

P5G41-M LE Memory Qualified Vendors List (QVL)

PM COPY

P5G41-M LE DDR2 1066 Qualified Vendors List (QVL)										
Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	socket support (Optional)	
									A*	B*
G.SKILL	F2-8500CL5D-4GBPI	DDR2 1066	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15			
Kingston	KHX8500D2K2/2G	DDR2 1066	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15			
Kingston	KHX8500D2K2/4G	DDR2 1066	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15			
Elixir	M2Y1G64TU88D5B-BD	DDR2 1066	1024MB	SS	Elixir	M2TU1G800E-BD	5		•	•

- 4 Dimm :
- **A\***: Supports [one module](#) inserted in any slot as Single-channel memory configuration
  - **B\***: Supports [2 modules](#) inserted into both the blue or black slots as two pairs of Dual-channel memory configuration

Note請按此鈕

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.